



**THE BEST WAY TO PROOF DUCT  
ELECTRONICALLY**

## **DUCT PROOFING BEACON NO. 71130**



*Drive the Duct Path*



*Duct Proofing*

## **ELECTRONICALLY PROOF TWO MILES OF DUCT IN MINUTES**

### **“PROOFING TOOL” FEATURES:**

- Locatable with most Cable Path Tracers and H. D. Tool Trackers\*
  - Air blow distance - 2 miles
  - Survives air blow proofing\*\*
  - Adaptable to Blow, Push, or Pull
  - Long range low-drag design
  - Good impact resistance
  - Water tight constructions
- \*Specify your tool      \*\*Must use catcher device

## **FINDS LOCATION OF DUCT PROBLEMS**

- Open couplings
- Pinch points
- Damaged duct
- Faulty duct extrusions
- Trace duct paths to find where they really go.
- Duct separations
- Severe bends
- Dirt and rubble in duct
- Faulty couplings

# Duct Proofing Beacon no. 71130

*THE BEST WAY TO PROOF DUCT - ELECTRONICALLY*

## EASY TO USE BY PROOFING CREW

### AIR BLOW "PROOFING TOOL" OPERATION

- 1) Install a tool catcher at the far end (a traffic cone packed with mule tape works well).
- 2) Clear the far end of the duct or manhole; the air blown device may be hazardous.
- 3) Turn on the "Proofing Tool" - verify it is "ON" with the cable path tracer or locator receiver.
- 4) Insert the "Proofing Tool" and projectile into the duct, projectile first.
- 5) Air blow the "Proofing Tool" through the duct.

### PROBLEM SOLVING

If the "Proofing Tool" does not arrive at the far end / manhole, follow the duct path with the locator to the position of the "Proofing Tool" (in most cases it can be found within 1 in. at a 4 ft. depth); the obstruction is approximately 12 inches ahead of the "Proofing Tool".

## "PROOFING TOOL" SPECIFICATIONS

### PHYSICALS

Length	5.0 in.
Diameter	1 in.
Weight	6.5 oz.

### PERFORMANCE

Locating Depth	25 ft.
Air Blow Distance	2 mi.
Battery Life	40 hrs. (CR2 camera battery)

## OTHER DUCT PROOFING PRODUCTS

- **Mandrels:** 1", 1-1/4", 1-1/2", 2", 3", 4" ( duct I.D. )
- **Projectiles:** 1", 1-1/4", 1-1/2", 2", 3", 4" ( duct I.D. )
- **Replacement Skirts:**
- **Rod-to-Proofing Tool Adapters**
- **Coiled Rods:** 0.25" and 0.375 dia.; length as needed



Important notice to purchasers: All statements, technical information and recommendations contained herein are based on information we believe to be reliable, but the accuracy and completeness thereof is not guaranteed. The following is made in lieu of all warranties, expressed or implied: Telemark Solutions™ Inc.'s obligation shall be to repair or replace any Telemark product proven to be defective within one year after shipment. Neither seller nor manufacturer shall be liable for injury, loss or damage, direct or consequential, arising out of the use of this product. User shall determine suitability of product for his intended use. User assumes all risk and liability in the use of the product. No statement or recommendation contained herein shall have any force or effect unless in an agreement signed by officers of Telemark Solutions™ Inc. Telemark is a trademark of Telemark Solutions™ Inc. Patents pending.

Telemark Solutions™  
302 Wright Drive  
Georgetown, Texas 78628  
Ph / Fax: 512-869-8855  
Email: [Telemark@texas.net](mailto:Telemark@texas.net)  
[www.telemarksolutions.com](http://www.telemarksolutions.com)